

PT 335SCC B Multi SLIT • CUT • CREASE • PERF • SCORE



Built on the same platform as the PT 8336SCC Multi, the PT 335SCC B Multi has all the same capabilities with the exception of strike perf, bar code reader and dual direction cut mark reader. This floor model, automatic feed/slit/cut/crease machine with a maximum sheet width of 13" can perform up to 32 creases per sheet, has a 4" vacuum pile feeder, 9" color touchscreen, lead edge cut mark reader, ultrasonic doubles detect and interchangeable crease/cross perf dies.

The PT 335SCC Multi series has a choice of five creasing widths, as well as an array of rotary tools for perforating and scoring. For strike perf option, bar code/OMR software, cut mark registration in both directions and up 400gsm paper thickness versus 350gsm, see model PT 8336SCC Multi.

FEATURES

- · Multi accessory output
- Interchangeable crease/ perf dies
- Linear rotary perf
- Built in job creator and 64 job program memory
- Automated crease depth adjustment
- Ultrasonic double sheet detection



SPECIFICATIONS

Minimum Stock Input Size Maximum Stock Input Size

Minimum Finished Output Size Maximum Finished Output Size

Paper Weight

Crease Depth Adjustment

Crease Width Options

Crease Direction Crease/Perforate Micro Perforating Feeding Method

Speed

Job Memory

Controls

Machine Weight

Machine Dimensions

Electrical

8.26" wide x 8.16" long (20.98cm x 20.72cm)

13" wide x 26.5" long (33.02cm x 67.31cm)

40" handfed (104cm)

1.96" x 1.89" (4.97cm x 4.8cm)

13" wide x 26" long (33.02cm x 66.04cm)

150-350 gsm

5 steps auto adjust

1mm standard (.4, .6, 1.2, 1.4mm options)

Up or down 0-32 per pass Yes 24/48 TPI

4" air suction pile feeder Up to 25 sheets per minute

64

9" colour touchscreen 380lbs (172.36kgs)

67"x 24"x 46" (170cm x 60.9cm x 116.8cm)

110V-130V, 60Hz, 15A

NOTE: Machine performance will vary based on stock weight, type, and specifications of the job being performed. WARRANTY: 3 year warranty (excludes consumables)

